

Thermal Slip Printer

XP-C300H

Printing speed : 300 mm/sec

Interface : USB + LAN + RS232



Features

- Front paper loading, vertical printing
- 300 MM/S printing speed
- Serial (RS232) + USB + LAN interface
- Built in web page to set up printer directly
- Printer status monitoring
- Input buffer 2048K bytes
- Support QR CODE printing
- Support LINUX, Windows system



ฝ่ายขายโทร : 084-905-5955

*ราคาขายอาจมีการเปลี่ยนแปลงได้โดยไม่แจ้งล่วงหน้า

บริษัท เพอร์เฟกต์ ซัพพลาย แอนด์โซลูชัน จำกัด (สำนักงานใหญ่)
68/18 ซอยอินทามระ 40 แขวงรัชดาภิเษก เขตดินแดง กรุงเทพมหานคร 10400

Line ID : @pssolution
Website : www.pssolution.com

@pssolution (มี @ นำหน้าด้วย)
PerfectSupplyAndSolution



'Xprinter XP-C300H' is new generation of receipt printer, waterproof, oilproof and dustproof design. With auto cutter and compatible with several operation systems.



Printing Preference

Printing	D300H
Printing method	Direct thermal
Print width	76mm
Column capacity	512 dots/line
Printing speed	300mm/s
Interface	USB+Serial+Lan
Printing paper	79.5±0.5mm x 80mm
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A : 1.5 x 3.0mm (12x24 dots) Font B : 1.1x2.1mm (9x17 dots) Chinese, traditional Chinese : 3.0x3.0mm (24x24 dots)

Cutter

Auto cutter	Partial
-------------	---------

Barcode Character

Extension character sheet	PC347 (Standard Europe), Katakana, PC850 (Multilingual), RC860 (Portuguese), PC863 (Canadian-French), PC865(Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), PC858, IranII, Latvian, Arabic, PT151 (1251)
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 / QR CODE / PDF417

Buffer

Input buffer	2048k bytes
NV Flash	256k bytes

Power

Power adaptor	Input: AC 110V/220V, 50-60Hz
Power source	Output: DC 24V/2.5A
Cash drawer output	DC 24V/1A

Physical characteristics

Weight	1.78KG
Dimensions	198x148x138mm (DxWxH)
Work environment	Temperature (0-45) humidity(10-80%)
Storage environment	Temperature(-10-60 C) humidity(10-80%)
Cutter life	1.5 million cuts
Printer head life	100KM

