



ZEBRA

ZD SERIES ZD220

Desktop Printer

ZD220 4-Inch

Reliable operation, quality construction,
unsurpassed value.



- Thermal Transfer or Direct Thermal print method
- ZPL and EPL programming languages
- Single LED status indicator
- Single button for feed/pause
- USB connectivity
- OpenACCESS™ for easy media loading
- Dual-wall frame construction
- ENERGY STAR qualified



ฝ่ายขายโทร : 084-905-5955

*ราคาขายอาจมีการเปลี่ยนแปลงได้โดยไม่แจ้งล่วงหน้า

บริษัท เพอร์เฟกต์ ซัพพลาย แอนด์โซลูชัน จำกัด (สำนักงานใหญ่)
68/18 ซอยอินทามระ 40 แขวงรัชดาภิเษก เขตดินแดง กรุงเทพมหานคร 10400

Line ID : @pssolution
Website : www.pssolution..com

@pssolution (มี @ นำหน้าด้วย)
PerfectSupplyAndSolution



SPECIFICATIONS

Standard Features	
Thermal Transfer or Direct Thermal print method ZPL and EPL programming languages Single LED status indicator Single button for feed/pause USB connectivity OpenACCESS™ for easy media loading Dual-wall frame construction ENERGY STAR qualified	
Physical Characteristics	
Dimension	Thermal Transfer: 10.5 in. L x 7.75 in. W x 7.5 in. H 267 mm L x 197 mm W x 191 mm H Direct Thermal: 8.6 in. L x 6.9 in. W x 5. in. H 220 mm L x 176 mm W x 151 mm H
Weight	2.5 lbs./1.1 kg
Printer Specifications	
Resolution*	203 dpi/8 dots per mm
Memory	256 MB Flash; 128 MB SDRAM
Maximum Print Width	4.09 in./104 mm
Maximum Print Speed	4 in./102 mm per second 9
Media Sensors	- Movable black mark sensor, limited range from center to left side - Fixed off-center gap sensor
Firmware	ZPL II; EPL 2; XML
Operating Characteristics	
Operating Temp.	40° to 105° F/4.4° to 41° C
Storage Temp.	-40° to 140° F/-40° to 60° C
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Electrical	Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz; ENERGY STAR qualified
Operations and Accessories	
Media Handling	Factory installed peeler
Real Time Clock	None
Fonts/Graphics/Symbologies	
Bar Code Ratios	2:1 and 3:1
1D Bar Codes	Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar and Planet Code
2D Bar Codes	Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, MicroPDF, Aztec
Fonts and Graphics	16 resident expandable ZPL II bitmap fonts Two resident scalable ZPL fonts Five resident expandable EPL2 fonts Native open-type font support Unicode compliant for multi-language, on demand thermal printing China units include SimSun simplified Chinese font 50 MB user available non-volatile memory, 8 MB user available SDRAM

Media and Ribbon Characteristics	
Maximum Label Length	39.0 in./991 mm
Media Width	1.00 in. / 25.4 mm to 4.4 in. / 112 mm
Media Roll Size	5.00 in./127 mm outer diameter Core inner diameter: 0.5 in. (12.7 mm) and 1.0 in. (25.4 mm) standard, 1.5 in. (38.1), 2.0 in., (50.8 mm) and 3.0 in. (76.2 mm) using optional adapters
Thickness	0.003 in. (0.08 mm) min.; 0.0075 in. (.1905 mm) max. (tear-off mode only)
Media Types	Roll-fed or fan-fold, die cut or continuous with or without black mark, tag stock, continuous receipt paper, and wristbands
Ribbon Outside Diameter	1.34 in./ 34 mm (74 m)
Maximum Ribbon Length	244 ft. (74 m)
Ribbon Ratio	1:1 media to ribbon (74 m)
Ribbon Width	1.33 in./ 33.8 mm ~ 4.3 in./ 109.2 mm
Ribbon Core I.D.	74 Meter ribbon 0.5 in./ 12.7 mm
Printers Supplies	
Keep your Zebra printer up and running with genuine Zebra printer supplies, available directly from Zebra.	
Regulatory	
- IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus - CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM	
Recommended Services	
Zebra OneCare SV	
Print DNA Software	
This printer is supported by a core set of PrintDNA applications powered by Link-OS® Basic.	
Print DNA features may vary by model and a Support Contract may be required. For more information, please visit www.zebra.com/printdna	
Product Warranty	
ZD200 series printers are warranted against defects in workmanship and materials for a period of 2 (two) years from the date of shipment. For the complete warranty statement, please visit: www.zebra.com/warranty .	



ฝ่ายขายโทร : 084-905-5955

*ราคาขายอาจมีการเปลี่ยนแปลงได้โดยไม่แจ้งล่วงหน้า

บริษัท เพอร์เฟกต์ ซัพพลาย แอนด์โซลูชัน จำกัด (สำนักงานใหญ่)
68/18 ซอยอินทามระ 40 แขวงรัชดาภิเษก เขตดินแดง กรุงเทพมหานคร 10400

Line ID : @pssolution
Website : www.pssolution..com

@pssolution (มี @ นำหน้าด้วย)
PerfectSupplyAndSolution

